

## Docking station

The docking station is used for charging and connecting the portable WBox\_Port terminal into the WIS system. The docking station contains a built-in TCP/IP communication unit. The portable terminal is connected to the docking station thanks to a contact field. The docking station is meant for mounting directly on the wall or different flat surface.



### Versions of the docking station

WIST0801

### Technical parameters

<b>Ethernet module</b>	WIZNET W7100A
<b>Protocol</b>	TCP, IP, UDP, ARP, ICMP, Ethernet MAC, Telnet TFTP, HTTP, SNMP
<b>Network interface – auto detection</b>	10/100 Base-T Ethernet
<b>Serial port</b>	RS485 - half duplex
<b>Transmitter control – RS 485</b>	TxD signal
<b>Data format</b>	8N1
<b>Data flow control</b>	None
<b>Transfer speed</b>	115kb/s
<b>Configuration</b>	Telnet login
<b>RS485 separation</b>	1kV
<b>Ethernet connector</b>	RJ45
<b>Supply connector</b>	Plug 1,3 mm
<b>Power supply</b>	9 – 50 DC, standardly supplied adapter 15V DC/1A
<b>Soft protection – power supply</b>	600W 10/1000us
<b>Input power</b>	max. 2 W
<b>Dimensions</b>	145 mm x 90 mm x 50 mm



## Dimensions

